



DECLARATION OF PERFORMANCE



DECLARATION OF PERFORMANCE CONTENTS

- **1. DECLARATION OF PERFORMANCE N°001**
- 2. DECLARATION OF PERFORMANCE N°003
- 3. DECLARATION OF PERFORMANCE N°004
- 4. DECLARATION OF PERFORMANCE N°006
- 5. DECLARATION OF PERFORMANCE N°007
- 6. DECLARATION OF PERFORMANCE N°008



ecoinalco

DECLARATION OF PERFORMANCE Nº 001

1. Unique identification code of the product type: Dry-pressed ceramic tiles with water absorption $E \leq 0,5\%$

- 2. Intended use/s: For internal and external floorings and walls
- 3. Manufacturer:

Industrias Alcorenses Confederadas, S.A. C/ San Salvador, 54, 12110 Alcora Castellón España

- 4. System/s of AVCP: System 4
- 5. Harmonised standard: EN 14411:2012
- 6. Notified body/ies: Not aplicable
- 7. Declared performances:

Essential characteristics	Performance
Reaction to fire	A1 _{PL} /A1
Release of dangerous substance, for:	
-Cadmium	NPD
-Lead	NPD
Breaking strength	>1.300 N
Slipperiness	NPD
Tactility	NPD
Bond strength/adhesion, for:	
Cementitius adhesive, type C2	>1 N/mm²
Thermal shock resistance	Pass
Durability for:	
- internal use	Pass
- external use: freeze-thaw resistance	Pass

The performance of the product identified above is in conformity with the set of declared performace/s. The declaration of performance is issued, in accordance with Regulation (EU) Nº 305/2011, under the sole responsability of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name and function: Sonia Damaret (QUALITY DEPARTMENT) Place and date of issue: Alcora, June 1st 2014 Signature:







DECLARATION OF PERFORMANCE Nº 003

1. Unic	ue	identifica	tio	m
water	ab	sorption	E	>

- 2. Intended use/s. For internal walls
- 3. Manufacturer:

Industrias Alcorenses Confederadas, S.A. C/ San Salvador, 54, 12110 Alcora Castellón España

- 4. System/s of AVCP: System 4

- 7. Declared performances:

Essential characteristics	Performance
Reaction to fire	A1
Release of dangerous substance, for:	
-Cadmium	NPD
-Lead	NPD
Breaking strength	NPD
Bond strength/adhesion	NPD
Durability for:	
- internal use	Pass

The performance of the product identified above is in conformity with the set of declared performace/s. The declaration of performance is issued, in accordance with Regulation (EU) Nº 305/2011, under the sole responsability of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name and function: Sonia Damaret (QUALITY DEPARTMENT) Place and date of issue: Alcora, June 1st 2014 Signature:





ecoinalco

code of the product type: Dry-pressed ceramic tiles with 10%

5. Harmonised standard: EN 14411:2012

6. Notified body/ies: Not aplicable





ecoinalco

DECLARATION OF PERFORMANCE Nº 004

1. Unique identification code of the product type: Dry-pressed ceramic tiles with water absorption $E \le 0,5\%$

SUMM

- 2. Intended use/s. For internal and external floorings and walls
- 3. Manufacturer:

Industrias Alcorenses Confederadas, S.A. C/ San Salvador, 54, 12110 Alcora Castellón España

- 4. System/s of AVCP: System 4
- 5. Harmonised standard: EN 14411:2012
- 6. Notified body/les: Not aplicable
- 7. Declared performances:

Essential characteristics	Performance
Reaction to fire	A1n./A1
Release of dangerous substance, for:	
-Cadmium	NPD
-Lead	NPD
Breaking strength	>700 N
Slipperiness	NPD
Tactility	NPD
Bond strength/adhesion, for:	
Cementitius adhesive, type C2	>1 N/mm²
Thermal shock resistance	Pass
Durability for:	
- internal use	Pass
 external use: freeze-thaw resistance 	Pass

The performance of the product identified above is in conformity with the set of declared performace/s. The declaration of performance is issued, in accordance with Regulation (EU) Nº 305/2011, under the sole responsability of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name and function: Sonia Damaret (QUALITY DEPARTMENT) Place and date of issue: Alcora, June 1st 2014 Signature:





	Unique identification ater absorption $E \leq$
2.	Intended use/s. For
3.	Manufacturer:
	Industrias Alcoren C/ San Salvador, 5
4.	System/s of AVCP: S
5.	Harmonised standard
6.	Notified body/ies: No

7. Declared performances:

Essential characteristics	Performance
Reaction to fire	A2n. S1
Release of dangerous substance, for:	
-Cadmlum	NPD
-Lead	NPD
Breaking strength	>1.300 N
Slipperiness	NPD
Tactility	NPD
Bond strength/adhesion, for:	
Cementitius adhesive, type C2	>1 N/mm ²
Thermal shock resistance	Pass
Durability for:	
- internal use	Pass
 external use: freeze-thaw resistance 	Pass

The performance of the product identified above is in conformity with the set of declared performace/s. The declaration of performance is issued, in accordance with Regulation (EU) Nº 305/2011, under the sole responsability of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Place and date of issue: Alcora, June 1st 2014 Signature:



ecoinalco

DECLARATION OF PERFORMANCE Nº 006

code of the product type: Dry-pressed ceramic tiles with 0,5%

internal and external floorings

nses Confederadas, S.A. 54, 12110 Alcora Castellón España

System 4

d: EN 14411:2012

lot aplicable

Name and function: Sonia Damaret (QUALITY DEPARTMENT)

INDUSTRIAS ALCORENSES CONFEDERADAS, S./ inalco ALCORA Castellén (Españo) N.I.F. A12008025



ecoinalco



DECLARATION OF PERFORMANCE Nº 007

- 1. Unique identification code of the product type: Dry-pressed ceramic tiles with water absorption $E \leq 0,5\%$
- 2. Intended use/s. For internal and external floorings and walls
- 3. Manufacturer:

Industrias Alcorenses Confederadas, S.A. C/ San Salvador, 54, 12110 Alcora Castellón España

- 4. System/s of AVCP: System 4
- 5. Harmonised standard: EN 14411:2012
- 6. Notified body/ies: Not aplicable
- 7. Declared performances:

Essential characteristics	Performance	
Reaction to fire	B s1 d0	
Release of dangerous substance, for:		
- Cadmium	PND	
- Lead	PND	
Breaking strength	>700 N	
Slipperiness	PND	
Tactility	PND	
Cementitius adhesive, type C2	>1 N/mm²	
Thermal shock resistance	Cumple	
Durability for:		
- internal use	Cumple	
- external use: freeze-thaw resistance	Cumple	

The performance of the product identified above is in conformity with the set of declared performace/s. The declaration of performance is issued, in accordance with Regulation (EU) Nº 305/2011, under the sole responsability of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name and function: Sonia Damaret (QUALITY DEPARTMENT) Place and date of issue: Alcora, September 2018 Signature:



1. Product:

IBASINS HYDRA 60x43

2. Intended use/s:

3. Manufacturer:

C/ San Salvador, 54 12110 Alcora Castellón España

4. System/s of AVCP:

System 4

5. Declared performances:

Essential characteristics	Performance	Harmonised technical specifications
Easy to clean	Pass	EN 14688-2006
Durability	Pass	EN 14688-2006

The performance of the product identified above is in conformity with the set of declared performace/s.

above.

Signed for and on behalf of the manufacturer by:

Name and function: Sonia Damaret (QUALITY DEPARTMENT) Place and date of issue: Alcora, December 7th 2018 Signature:



ecoinalco

DECLARATION OF PERFORMANCE Nº 008

DOMESTIC USE FOR PERSONAL HYGIENE

INDUSTRIAS ALCORENSES CONFEDERADAS, S.A.

The declaration of performance is issued under the sole responsability of the manufacturer identified





INDUSTRIAS ALCORENSES CONFEDERADAS S.A. C/ San Salvador, 54 12110, Alcora, Castellón (España) (+34) 964 368 000 www.inalco.es_www.inalcotrends.com

