



European
Ceramics

FRAMEWORK RANGE

Product Name: **FRAMEWORK - VARIOUS COLOURS/FINISHES/SIZES/THICKNESS**

Product Identifier: Refer to tile name and product code on paperwork/packaging

Product Description: A glazed porcelain tile and a water absorption rate of less than 0.50%.

Country Of Origin: Italy

Building Code Obligations

Code Clauses:

B2 – Durability

B2.3.1

C3 – Fire affecting areas beyond the
source

D1 – Access routes

D1.3.3

E3 – Internal moisture

E3.3.2, 3.3.3, 3.3.4

G3 – Food preparation and prevention of
contamination

G3.3.2

G6 – Airborne and Impact sound

G6.3.1



Note – this building product is not subject to a warning/ban under section 26 of the Building Act 2004

Manufacturer Details:

European Ceramics Approved

BPIR COMPLIANT

Importer Details:

European Ceramic Tiles Ltd

Address: 7A Cowley Place, Rosedale, AKL 0632

NZBN: 9429037294571

Website: euroceramics.co.nz

Scope	Use
B2 Durability	See below suitability table
C3 Fire	The Building Code relating to fire ratings regulation & standards become mandatory from April 2013, establishing the list of products belonging to Classes A 'No Contribution to Fire' provided for in Decision 94/611/EC implementing Article 20 of Council Directive 89/106/EEC.
D1 Access Routes	Refer to slip resistance documentation for all Access routes classifications D1/AS1 for above range.
E3 Internal Moisture	Under E3 Tiles installed over a waterproof membrane using a nonporous grouting system, are an acceptable solution.
G3 Food Preparation & Prevention from Contamination	As an impervious and easy to clean surface, this range complies.
G6 Airborne & Impact Sound	If required, tiles can form part of an acoustic system to comply with IIC & STC in conjunction with an approved third-party system.

Suitability *	Residential	Light Commercial	Commercial
Indoor Floor	*	*	*
Indoor Walls	*	*	*
Outdoor Cladding	*	*	*
Frost Resistant	*	*	*
Swimming Pool Submerged	*	*	*
Swimming Pool Surround	*	*	*
Paving/External	*	*	*
Over Underfloor Heating	*	*	*
Kitchen wall	*	*	*
Within 1.5m of a Plumbing Fixture or Fitting	*	*	*

Manufacturer Details:
European Ceramics Approved
BPIR COMPLIANT

Importer Details:
European Ceramic Tiles Ltd
Address: 7A Cowley Place, Rosedale, AKL 0632
NZBN: 9429037294571
Website: euroceramics.co.nz

Building Code References

B2 – Durability

Compliance with B2 Durability is about providing evidence that the product will meet the relevant durability life in the context of the environment in which it will be located.

The building code sets out the framework for establishing the relevant durability life of building elements based on a number of criteria. B2/AS1 provides a decision tree to establish the relevant durability for common building materials in different circumstances.

Having determined the durability life of the product, the next step is to determine if the product, when exposed to the environment, will continue to perform for the relevant period. A key tool which a product supplier can consider in claiming compliance is limiting the environment in which the product will be exposed to (e.g. a ferrous material used in an indoor environment will last longer than it would when exposed to salt spray — in this example it would be appropriate for the supplier to condition the compliance information to use only in indoor environments).

C3 – Fire affecting areas beyond the source

C3 Fire affecting areas beyond the fire source is primarily about ensuring that fire does not spread from a fire in the building (in both vertically and horizontally) and from an adjacent building.

The prime product attribute used is the fire resistance rating (FRR) methodology. In most cases a product is combined with other products to achieve a FRR (e.g. an external wall fire rating may be formed by the combination of the external cladding, thermal insulation and the internal lining).

C/AS1 and C/AS2 set out performance criteria for buildings and in particular the FRR requirements for various types of buildings and parts of buildings. Appendix C of C/AS2 sets out test methods for the building elements involved in spread of fire. Appendix B of C/AS2 sets out performance criteria for sprinkler systems while Appendix A sets out criteria for fire safety systems such as alarms and hydrants.

D1 – Access routes

For D1 access routes, in most cases product-related compliance for access routes is slip resistance for floors and the shapes/locations etc of handrails. The Acceptable Solution for access D1/AS1 and NZS 4121:2001 provide good information on compliance for products on access routes.

E3 – Internal Moisture

E3 Internal Moisture is about ensuring that moisture created within the building does not lead to mould or create damage to adjacent buildings or structural elements in the building in which it is installed.

Prevention of the creation of mould is a combination of temperature, insulation and ventilation. Prevention of water damaging other building elements is mainly about installation details (i.e. sealing joints) as well as impervious products. E3/AS1 provides some useful design details, albeit without much product material information.

Manufacturer Details:
European Ceramics Approved
BPIR COMPLIANT

Importer Details:
European Ceramic Tiles Ltd
Address: 7A Cowley Place, Rosedale, AKL 0632
NZBN: 9429037294571
Website: euroceramics.co.nz

G3 – Food preparation and prevention of contamination

G3 Food preparation and prevention from contamination for a product (such as a kitchen bench) is mainly associated with being easily cleaned and impervious. G3/AS1 provides some general design details for food preparation areas but has no referenced product standards, although the document does state some acceptable materials used for surfaces. Compliance with G3/AS1 is not mandatory but provides a good benchmark for compliance.

G6 – Airborne and Impact Sound

For a product, G6 Airborne and impact sound is generally about systems which are designed to work together to achieve the necessary sound attenuation.

The code itself at G6.3.2 sets a quantifiable performance level: “The Sound Transmission Class of walls, floors and ceilings, shall be no less than 55” and G6.3.2 sets the impact insulation class of floors shall be no less than 55. The Acceptable Solution G6/AS1 sets out the transmission and impact insulation class of common wall systems. G6/VM1 sets out test methodologies where the details do not match those of G6/AS1.

Manufacturer Details:
European Ceramics Approved
BPIR COMPLIANT

Importer Details:
European Ceramic Tiles Ltd
Address: 7A Cowley Place, Rosedale, AKL 0632
NZBN: 9429037294571
Website: euroceramics.co.nz

Technical Information

PORCELAIN TILES WITH COLOURED BODY DIGITAL

R10 B
PRO

R11
outdoor

V2



COLOURS



white



grey



beige



taupe



dust

SURFACES



PRO



outdoor

SIZES



60x119,8 | 24"x48"
rect
⌀8,2 mm

PRO
outdoor



60x60 | 24"x24"
rect
⌀8,2 mm

PRO
outdoor




30x60 | 12"x24"
rect
⌀8,2 mm

PRO
outdoor



30x30 | 12"x12"
mosaico
⌀8,2 mm



60x119,8 | 24"x48"
hexagon dec rect
⌀8,2 mm

DIGITAL
REAL

PACKING	⌀ mm	pcs/box	sqm/box	kg/sqm	box/plt	sqm/plt	kg/plt
60x119,8 24"x48" rect	8,2	2	1,44	16,20	42	60,48	1005
60x60 24"x24" rect	8,2	4	1,44	16,20	32	46,08	771
30x60 12"x24" rect	8,2	8	1,44	16,20	40	57,60	958
30x30 12"x12" mosaico	8,2	11	1,00	16,20	30	30,00	511
7,5x60 3"x24" battiscopa rect	8,2	16	-	-	-	-	-

Manufacturer Details:
European Ceramics Approved
BPIR COMPLIANT

Importer Details:
European Ceramic Tiles Ltd
Address: 7A Cowley Place, Rosedale, AKL 0632
NZBN: 9429037294571
Website: euroceramics.co.nz

STONE SET

TECHNICAL CHARACTERISTIC CARATTERISTICA TECNICA CARACTERISTIQUE TECHNIQUE TECHNISCHE EIGENSCHAFT	REFERENCE STANDARD NORMA DI RIFERIMENTO NORME DE REFERENCE BEZUGSNORM	VALUE REQUIRED VALORE RICHIESTO VALEUR REQUISE GEFORDERTER WERT	ACCORDANCE TO THE NORME RISPONDERENZA ALLA NORMA CORRESPONDANCE À LA NORME ÜBEREINSTIMMUNG MIT DER NORM	
water absorption (E) assorbimento d'acqua (E) absorption d'eau (E) Feuchtigkeitsaufnahme (E)	 ISO 10545-3	≤ 0,5%	according to conforme conformes Gemäß	
breaking strength (S) forza di rottura (S) contrainte de rupture (S) Bruchkraft (S)	 ISO 10545-4	thickness ≥ 7,5 mm ≥ 1300 N thickness < 7,5 mm ≥ 700 N	according to conforme conformes Gemäß	
bending strength (R) resistenza alla flessione (R) résistance à la flexion (R) mechanischer widerstand (R)	 ISO 10545-4	≥ 35 N/mm ²	according to conforme conformes Gemäß	
deep abrasion resistance resistenza all'abrasione profonda résistance à l'usure en profondeur Tiefen-Abriebbeständigkeit	 ISO 10545-6	≤ 175 mm ³	according to conforme conformes Gemäß	
thermal shock resistance resistenza agli sbalzi termici résistance aux écarts de température Temperaturwechselbeständigkeit	 ISO 10545-9	no sample must show visible defects nessun campione deve presentare difetti visibili aucun échantillon ne doit présenter des défauts visibles Kein Exemplar soll sichtbare Schäden aufweisen	according to conforme conformes Gemäß	
frost resistance resistenza al gelo résistance au gel Frostbeständigkeit	 ISO 10545-12	resistant résistants Widerstandsfähig	resistant résistants Widerstandsfähig	
anti-slip resistance grade fattore di resistenza alla scivolosità gré de résistance à la glissance Rutschfestigkeit	 DIN EN 16165 ANNEX B	according to producer's secondo i dati del costruttore selon les éléments du constructeur laut Angaben des Herstellers	R10 PRO R11 outdoor	
slip resistance factor in the presence of water and bare feet fattore di resistenza alla scivolosità in presenza di acqua a piedi nudi facteur de résistance à la glissance pieds nus en présence d'eau Rutschfestigkeit im Nassbereich beim Gehen mit bloßen Füßen	 DIN EN 16165 ANNEX A	according to producer's secondo i dati del costruttore selon les éléments du constructeur laut Angaben des Herstellers	B PRO	
size characteristics caratteristiche dimensionali caractéristiques dimensionnelles Maßeigenschaften	 ISO 10545-2	length and width / lunghezza e larghezza / longueur et largeur / Länge und Breite thickness / spessore / épaisseur / Stärke wedging / ortogonalità / orthogonalité / Rechtwinkligkeit flatness / planarità / planéité / Ebenförmigkeit	± 0,6% (max ± 2 mm) ± 5,0% (max ± 0,5 mm) ± 0,5% (max ± 2 mm) ± 0,5% (max ± 2 mm)	according to conforme conformes Gemäß
linear thermal expansion coefficient coefficiente di dilatazione termica lineare coefficient de expansion thermique linear Wärmeausdehnungskoeffizient	 ISO 10545-8	test method available metodo di prova disponibile méthode d'essai disponible Verfügbare Prüfmethode	α ≤ 7 x 10 ⁻⁶ /°C	
resistance to chemicals resistenza ai prodotti chimici résistance aux produits chimiques Chemikalbeständigkeit	 ISO 10545-13	min. B	according to conforme conformes Gemäß	
stain resistance resistenza alle macchie résistance aux taches Fleckenbeständigkeit	 ISO 10545-14	class ≥ 3	according to conforme conformes Gemäß	

Fire Resistance

The building code relating to fire rating regulations and standards requires specifiers to provide documentation such as fire certificates for materials used in construction.

Ceramics are in itself a fire-resistant material, mostly being manufactured at over 1200 degrees Celsius. Testing and providing such certification are therefore not relevant to the Ceramics industry.

Ceramic and Porcelain tiles are an inert material, and therefore non-combustible. They do not release fumes or toxic gases in the event of a fire. Porcelain tiles contain no sealants, waxes or other chemicals that could release VOC's into the environment. Ceramics do not pose a risk of spreading or intensifying a fire therefore there is no testing required as they do not contribute to a fire.

EXTRAORDINARY EFFECTS DURING USE PHASE:

Fire: According to /EN 13501-1:2007+A1:2009/, ceramic tiles can be classified as A1 class of fire resistance rating, because they do not contribute to fire.

It has been demonstrated that the coating of the ceramic tiles, in case of fire, reduces heat on them and thus the risk of collapse.

Water: Ceramic tiles cannot react with water because they are an insoluble material.

For further information on the fire performance characteristics of ceramic/porcelain tiles or natural stone, please refer to the Technical Documents section on euroceramics.co.nz

Manufacturer Details:

European Ceramics Approved

BPIR COMPLIANT

Importer Details:

European Ceramic Tiles Ltd

Address: 7A Cowley Place, Rosedale, AKL 0632

NZBN: 9429037294571

Website: euroceramics.co.nz