



European
Ceramics

DORSET RANGE

Product Name: **DORSET - VARIOUS COLOURS/FINISHES**

Product Identifier: Refer to tile name and product code on paperwork/packaging

Product Description: A glazed porcelain tile and a water absorption rate of less than 0.50%.

Country Of Origin: Italy

Building Code Obligations

Code Clauses:

B2 – Durability

B2.3.1

C3 – Fire affecting areas beyond the source

D1 – Access routes

D1.3.3

E3 – Internal moisture

E3.3.2, 3.3.3, 3.3.4

G3 – Food preparation and prevention of contamination

G3.3.2

G6 – Airborne and Impact sound

G6.3.1



Note – this building product is not subject to a warning/ban under section 26 of the Building Act 2004

Manufacturer Details:

European Ceramics Approved

BPIR COMPLIANT

Importer Details:

European Ceramic Tiles Ltd

Address: 7A Cowley Place, Rosedale, AKL 0632

NZBN: 9429037294571

Website: euroceramics.co.nz

Scope	Use
B2 Durability	See below suitability table
C3 Fire	The Building Code relating to fire ratings regulation & standards become mandatory from April 2013, establishing the list of products belonging to Classes A 'No Contribution to Fire' provided for in Decision 94/611/EC implementing Article 20 of Council Directive 89/106/EEC.
D1 Access Routes	Refer to slip resistance documentation for all Access routes classifications D1/AS1 for above range.
E3 Internal Moisture	Under E3 Tiles installed over a waterproof membrane using a nonporous grouting system, are an acceptable solution.
G3 Food Preparation & Prevention from Contamination	As an impervious and easy to clean surface, this range complies.
G6 Airborne & Impact Sound	If required, tiles can form part of an acoustic system to comply with IIC & STC in conjunction with an approved third-party system.

<i>Suitability *</i>	<i>Residential</i>	<i>Light Commercial</i>	<i>Commercial</i>
Indoor Floor	*	*	*
Indoor Walls	*	*	*
Outdoor Cladding	*	*	*
Frost Resistant	*	*	*
Swimming Pool Submerged	*	*	*
Swimming Pool Surround	*	*	*
Paving/External	*	*	*
Over Underfloor Heating	*	*	*
Kitchen wall	*	*	*
Within 1.5m of a Plumbing Fixture or Fitting	*	*	*

Manufacturer Details:

European Ceramics Approved

BPIR COMPLIANT

Importer Details:
 European Ceramic Tiles Ltd
 Address: 7A Cowley Place, Rosedale, AKL 0632
 NZBN: 9429037294571
 Website: euroceramics.co.nz

Building Code References

B2 – Durability

Compliance with B2 Durability is about providing evidence that the product will meet the relevant durability life in the context of the environment in which it will be located.

The building code sets out the framework for establishing the relevant durability life of building elements based on a number of criteria. B2/AS1 provides a decision tree to establish the relevant durability for common building materials in different circumstances.

Having determined the durability life of the product, the next step is to determine if the product, when exposed to the environment, will continue to perform for the relevant period. A key tool which a product supplier can consider in claiming compliance is limiting the environment in which the product will be exposed to (e.g. a ferrous material used in an indoor environment will last longer than it would when exposed to salt spray — in this example it would be appropriate for the supplier to condition the compliance information to use only in indoor environments).

C3 – Fire affecting areas beyond the source

C3 Fire affecting areas beyond the fire source is primarily about ensuring that fire does not spread from a fire in the building (in both vertically and horizontally) and from an adjacent building.

The prime product attribute used is the fire resistance rating (FRR) methodology. In most cases a product is combined with other products to achieve a FRR (e.g. an external wall fire rating may be formed by the combination of the external cladding, thermal insulation and the internal lining).

C/AS1 and C/AS2 set out performance criteria for buildings and in particular the FRR requirements for various types of buildings and parts of buildings. Appendix C of C/AS2 sets out test methods for the building elements involved in spread of fire. Appendix B of C/AS2 sets out performance criteria for sprinkler systems while Appendix A sets out criteria for fire safety systems such as alarms and hydrants.

D1 – Access routes

For D1 access routes, in most cases product-related compliance for access routes is slip resistance for floors and the shapes/locations etc of handrails. The Acceptable Solution for access D1/AS1 and NZS 4121:2001 provide good information on compliance for products on access routes.

E3 – Internal Moisture

E3 Internal Moisture is about ensuring that moisture created within the building does not lead to mould or create damage to adjacent buildings or structural elements in the building in which it is installed.

Prevention of the creation of mould is a combination of temperature, insulation and ventilation. Prevention of water damaging other building elements is mainly about installation details (i.e. sealing joints) as well as impervious products. E3/AS1 provides some useful design details, albeit without much product material information.

Manufacturer Details:

European Ceramics Approved

BPIR COMPLIANT

Importer Details:

European Ceramic Tiles Ltd

Address: 7A Cowley Place, Rosedale, AKL 0632

NZBN: 9429037294571

Website: euroceramics.co.nz

G3 – Food preparation and prevention of contamination

G3 Food preparation and prevention from contamination for a product (such as a kitchen bench) is mainly associated with being easily cleaned and impervious. G3/AS1 provides some general design details for food preparation areas but has no referenced product standards, although the document does state some acceptable materials used for surfaces. Compliance with G3/AS1 is not mandatory but provides a good benchmark for compliance.

G6 – Airborne and Impact Sound

For a product, G6 Airborne and impact sound is generally about systems which are designed to work together to achieve the necessary sound attenuation.

The code itself at G6.3.2 sets a quantifiable performance level: “The Sound Transmission Class of walls, floors and ceilings, shall be no less than 55” and G6.3.2 sets the impact insulation class of floors shall be no less than 55. The Acceptable Solution G6/AS1 sets out the transmission and impact insulation class of common wall systems. G6/VM1 sets out test methodologies where the details do not match those of G6/AS1.

Manufacturer Details:

European Ceramics Approved

BPIR COMPLIANT

Importer Details:

European Ceramic Tiles Ltd

Address: 7A Cowley Place, Rosedale, AKL 0632

NZBN: 9429037294571

Website: euroceramics.co.nz

Technical Information

TECHNICAL SPECIFICATIONS PORCELAIN STONEWARE

TECHNISCHE EIGENSCHAFTEN FEINSTEINZEUG / CARACTÉRISTIQUES TECHNIQUES GRES CÉRAME

CONFORME A NORME / CONFORMING TO STANDARDS / GEMÄSS DEN NORMEN / CONFORMES AUX NORMES

EN 14411 ISO 13006 APPENDICE G GRUPPO B1a UGL CON Ev ≤ 0,5%

CARATTERISTICA TECNICA PHYSICAL PROPERTIES TECHNISCHE DATEN CARACTÉRISTIQUE TECHNIQUE	METODICA DI PROVA TESTING METHOD PRÜFVERFAHREN NORME D'ESSAIS	RIFERIMENTO NORMA REFERENCE STANDARD REFERENCE NORME STANDARDWERT	VALORE PRODOTTO PRODUCT VALUES PRODUKT WERTE VALEUR PRODUIT
Dimensioni Size Abmessungen Dimensions	EN ISO 10545-2	7cm ≤ N < 15 cm (mm) Lunghezza e larghezza - Length and width Länge und Breite - Longueur et largeur Spessore - Thickness - Stärke - Epaisseur Rettolineità spigoli - Linearity Kantengenauigkeit - Rectitude des arêtes Ortogonalità - Wedging Rechtwinkligkeit - Orthogonalité Planeritá - Warpage - Ebenflächigkeit - Planéité	N ≥ 15 cm (mm) ±0.9 ±0.6 ±2.0 ±0.5 ±5.0 ±0.5 ±0.75 ±0.5 ±1.5 ±0.75 ±0.5 ±2.0 ±0.75 ±0.5 ±2.0
		Aspetto: percentuale di piastrelle accettabili nel lotto - Appearance: percentage of acceptable tiles per lot - Oberflächenbeschaffenheit: prozentzahl der fliesen, die den geforderten eigenschaften entsprechen Aspect: pourcentage de carreaux acceptables sur la livraison totale	95 % min. 95 % min.
 Assorbimento d'acqua % - Water absorption % Wasserabsorption % - Absorption d'eau %	EN ISO 10545-3	Ev ≤ 0,5%	Conforme - Conforming Erfüllt - Conforme
 Resistenza alla flessione - Modulus of rupture Biegezugfestigkeit - Résistance à la flexion	EN ISO 10545-4	Valore medio 35 N/mm2 min. sp. > = 7,5 mm: min 1300 N sp. < 7,5 mm: min 700 N	Conforme - Conforming Erfüllt - Conforme
 Resistenza all'abrasione profonda - Deep abrasion resistance - Bestimmung des Widerstandes gegen tiefen Verschleiß - Résistance à l'abrasion	EN ISO 10545-6	175 mm3 max.	Conforme - Conforming Erfüllt - Conforme Medio - Average Mittelwert - Moyenne < 150 mm3
 Coefficiente di dilatazione termica lineare - Thermal expansion coefficient - Wärmedehnungsmaß - Coefficient de dilatation thermique linéaire	EN ISO 10545-8	Valore dichiarato - Declared value Angegebener Wert - Valeur déclarée	6,8 MK-1
 Resistenza agli sbalzi termici - Thermal shock resistance - Temperaturwechselbeständigkeit - Résistance aux écarts de température	EN ISO 10545-9	Test superato in accordo con ISO 10545-1 - Pass according to ISO 10545-1 Test überstanden nach ISO 10545-1 - Pas en accord avec norme en 10545-1	* Resistente - Resistant Widerstandsfähig - Résistants
 Resistenza al gelo - Frost resistance Frostbeständigkeit - Résistance au gel	EN ISO 10545-12	Test superato in accordo con ISO 10545-1 - Pass according to ISO 10545-1 Test überstanden nach ISO 10545-1 - Pas en accord avec norme en 10545-1	* Resistente - Resistant Widerstandsfähig - Résistants
		Valore dichiarato - Declared value Angegebener Wert - Valeur déclarée	*
 Resistenza ad alte concentrazioni di acidi e alcali Resistance to high concentrations of acids and alkali - Beständigkeit gegen schwach konzentrierte sauren und laugen - Résistance à des hautes concentrations d'acides et bases	EN ISO 10545-13	Valore dichiarato - Declared value Angegebener Wert - Valeur déclarée	*
		UB min.	UA
 Resistenza alle macchie di piastrelle non smaltite naturali - Stain resistance of unglazed matte porcelain Fleckenbeständigkeit von unglasierten natur Fliesen - Résistance aux taches des carreaux non émaillés naturel	EN ISO 10545-14	Valore dichiarato - Declared value Valeur déclarée - Angegebener Wert	*
	DIN 51130		Valore disponibile a richiesta Value available upon request Wert auf Anfrage verfügbar Valeur disponible sur demande
 Resistenza alla scivolosità Slip resistance Rutschfestigkeit Résistance au dérapage	DIN 51097	Dove richiesto - If needed - Nach anforderung - Si demande	Valore disponibile a richiesta Value available upon request Wert auf Anfrage verfügbar Valeur disponible sur demande
			> 0.40 Dry / > 0.40 Wet ≥ 0.42 Wet
	B.C.R.A. - D.M.236/ 89 ANSI A326.3 D COF		

Manufacturer Details:

European Ceramics Approved

BPIR COMPLIANT

Importer Details:
European Ceramic Tiles Ltd
Address: 7A Cowley Place, Rosedale, AKL 0632
NZBN: 9429037294571
Website: euroceramics.co.nz

Technical Info

GRES PORCELLANATO - RETTIFICATO PORCELAIN STONEWARE - RECTIFIED

CONFORMING TO STANDARDS
EN 14411 ISO 13006 APPENDICE G GRUPPO Bla UGL CON Ev \leq 0,5%



BENDING
STRENGTH



FROST
RESISTANCE



CHEMICALS
RESISTANCE



STAIN
RESISTANCE

ADVANCED TECHNOLOGY



WEBSITE

StrideUp®

RealUp®



ANSI A326.3 > 0,42
REALUP / STRIDEUP



R10 / A + B
REALUP / STRIDEUP



ANSI A326.3 > 0,42
NATURALE / MATTE



ANSI A326.3 > 0,42
ANTISLIP
OPEN



R11 / A+B+C
ANTISUP
OPEN



HEAVY TRAFFIC
TRAFFICO INTENSO
Naturale / Matte
RealUp / StrideUp
Antislip
OPEN



V2
MODERATE
All Colours

Fire Resistance

The building code relating to fire rating regulations and standards requires specifiers to provide documentation such as fire certificates for materials used in construction.

Ceramics are in itself a fire-resistant material, mostly being manufactured at over 1200 degrees Celsius. Testing and providing such certification are therefore not relevant to the Ceramics industry.

Ceramic and Porcelain tiles are an inert material, and therefore non-combustible. They do not release fumes or toxic gases in the event of a fire. Porcelain tiles contain no sealants, waxes or other chemicals that could release VOC's into the environment. Ceramics do not pose a risk of spreading or intensifying a fire therefore there is no testing required as they do not contribute to a fire.

EXTRAORDINARY EFFECTS DURING USE PHASE:

Fire: According to /EN 13501-1:2007+A1:2009/, ceramic tiles can be classified as A1 class of fire resistance rating, because they do not contribute to fire.

It has been demonstrated that the coating of the ceramic tiles, in case of fire, reduces heat on them and thus the risk of collapse.

Water: Ceramic tiles cannot react with water because they are an insoluble material.

Manufacturer Details:

European Ceramics Approved

BPIR COMPLIANT

Importer Details:

European Ceramic Tiles Ltd

Address: 7A Cowley Place, Rosedale, AKL 0632

NZBN: 9429037294571

Website: euroceramics.co.nz

**For further information on the physio-characteristics of fire resistance for tiles please refer to
the Technical Documents section on euroceramics.co.nz**

Manufacturer Details:

European Ceramics Approved

BPIR COMPLIANT

Importer Details:

European Ceramic Tiles Ltd

Address: 7A Cowley Place, Rosedale, AKL 0632

NZBN: 9429037294571

Website: euroceramics.co.nz