



European
Ceramics

COMPATTA RANGE

Product Name: **COMPATTA - VARIOUS COLOURS/FINISHES/SIZES/THICKNESS**

Product Identifier: Refer to tile name and product code on paperwork/packaging

Product Description: A glazed porcelain tile and a water absorption rate of less than 0.50%.

Country Of Origin: Italy

Building Code Obligations

Code Clauses:

B2 – Durability

B2.3.1

C3 – Fire affecting areas beyond the
source

D1 – Access routes

D1.3.3

E3 – Internal moisture

E3.3.2, 3.3.3, 3.3.4

G3 – Food preparation and prevention of
contamination

G3.3.2

G6 – Airborne and Impact sound

G6.3.1



Note – this building product is not subject to a warning/ban under section 26 of the Building Act 2004

Manufacturer Details:

European Ceramics Approved

BPIR COMPLIANT

Importer Details:

European Ceramic Tiles Ltd

Address: 7A Cowley Place, Rosedale, AKL 0632

NZBN: 9429037294571

Website: euroceramics.co.nz

Scope	Use
B2 Durability	See below suitability table
C3 Fire	The Building Code relating to fire ratings regulation & standards become mandatory from April 2013, establishing the list of products belonging to Classes A 'No Contribution to Fire' provided for in Decision 94/611/EC implementing Article 20 of Council Directive 89/106/EEC.
D1 Access Routes	Refer to slip resistance documentation for all Access routes classifications D1/AS1 for above range.
E3 Internal Moisture	Under E3 Tiles installed over a waterproof membrane using a nonporous grouting system, are an acceptable solution.
G3 Food Preparation & Prevention from Contamination	As an impervious and easy to clean surface, this range complies.
G6 Airborne & Impact Sound	If required, tiles can form part of an acoustic system to comply with IIC & STC in conjunction with an approved third-party system.

<i>Suitability *</i>	<i>Residential</i>	<i>Light Commercial</i>	<i>Commercial</i>
Indoor Floor	*	*	*
Indoor Walls	*	*	*
Outdoor Cladding	*	*	*
Frost Resistant	*	*	*
Swimming Pool Submerged	*	*	*
Swimming Pool Surround	*	*	*
Paving/External	*	*	*
Over Underfloor Heating	*	*	*
Kitchen wall	*	*	*
Within 1.5m of a Plumbing Fixture or Fitting	*	*	*

Manufacturer Details:
European Ceramics Approved
BPIR COMPLIANT

Importer Details:
European Ceramic Tiles Ltd
Address: 7A Cowley Place, Rosedale, AKL 0632
NZBN: 9429037294571
Website: euroceramics.co.nz

Building Code References

B2 – Durability

Compliance with B2 Durability is about providing evidence that the product will meet the relevant durability life in the context of the environment in which it will be located.

The building code sets out the framework for establishing the relevant durability life of building elements based on a number of criteria. B2/AS1 provides a decision tree to establish the relevant durability for common building materials in different circumstances.

Having determined the durability life of the product, the next step is to determine if the product, when exposed to the environment, will continue to perform for the relevant period. A key tool which a product supplier can consider in claiming compliance is limiting the environment in which the product will be exposed to (e.g. a ferrous material used in an indoor environment will last longer than it would when exposed to salt spray — in this example it would be appropriate for the supplier to condition the compliance information to use only in indoor environments).

C3 – Fire affecting areas beyond the source

C3 Fire affecting areas beyond the fire source is primarily about ensuring that fire does not spread from a fire in the building (in both vertically and horizontally) and from an adjacent building.

The prime product attribute used is the fire resistance rating (FRR) methodology. In most cases a product is combined with other products to achieve a FRR (e.g. an external wall fire rating may be formed by the combination of the external cladding, thermal insulation and the internal lining).

C/AS1 and C/AS2 set out performance criteria for buildings and in particular the FRR requirements for various types of buildings and parts of buildings. Appendix C of C/AS2 sets out test methods for the building elements involved in spread of fire. Appendix B of C/AS2 sets out performance criteria for sprinkler systems while Appendix A sets out criteria for fire safety systems such as alarms and hydrants.

D1 – Access routes

For D1 access routes, in most cases product-related compliance for access routes is slip resistance for floors and the shapes/locations etc of handrails. The Acceptable Solution for access D1/AS1 and NZS 4121:2001 provide good information on compliance for products on access routes.

E3 – Internal Moisture

E3 Internal Moisture is about ensuring that moisture created within the building does not lead to mould or create damage to adjacent buildings or structural elements in the building in which it is installed.

Prevention of the creation of mould is a combination of temperature, insulation and ventilation. Prevention of water damaging other building elements is mainly about installation details (i.e. sealing joints) as well as impervious products. E3/AS1 provides some useful design details, albeit without much product material information.

Manufacturer Details:

European Ceramics Approved

BPIR COMPLIANT

Importer Details:

European Ceramic Tiles Ltd

Address: 7A Cowley Place, Rosedale, AKL 0632

NZBN: 9429037294571

Website: euroceramics.co.nz

G3 – Food preparation and prevention of contamination

G3 Food preparation and prevention from contamination for a product (such as a kitchen bench) is mainly associated with being easily cleaned and impervious. G3/AS1 provides some general design details for food preparation areas but has no referenced product standards, although the document does state some acceptable materials used for surfaces. Compliance with G3/AS1 is not mandatory but provides a good benchmark for compliance.

G6 – Airborne and Impact Sound

For a product, G6 Airborne and impact sound is generally about systems which are designed to work together to achieve the necessary sound attenuation.

The code itself at G6.3.2 sets a quantifiable performance level: “The Sound Transmission Class of walls, floors and ceilings, shall be no less than 55” and G6.3.2 sets the impact insulation class of floors shall be no less than 55. The Acceptable Solution G6/AS1 sets out the transmission and impact insulation class of common wall systems. G6/VM1 sets out test methodologies where the details do not match those of G6/AS1.

Manufacturer Details:
European Ceramics Approved
BPIR COMPLIANT

Importer Details:
European Ceramic Tiles Ltd
Address: 7A Cowley Place, Rosedale, AKL 0632
NZBN: 9429037294571
Website: euroceramics.co.nz

Technical Information

COMPATTA

I formati delle lastre ceramiche

The sizes in the ceramic slab range

	Spessore Thickness	Applicazione Application	Finitura Finish	120 x 280 cm 47 1/8" x 110 1/4"	120 x 240 cm 47 1/8" x 94 3/8"	120 x 120 cm 47 1/8" x 47 1/8"	60 x 120 cm 23 5/8" x 47 1/8"
Sabbia 	9 mm 3/8"		Opaco Matt		778092	777974	777978
Limo 	9 mm 3/8"		Opaco Matt		778093	777975	777979
Argilla 	9 mm 3/8"		Opaco Matt		778094	777976	777980
Ghiaia 	9 mm 3/8"		Opaco Matt		778095	777977	777981
Pisé Sabbia 	6 mm 1/4"		Opaco Matt	777970			
	9 mm 3/8"		Opaco Matt				777953
Pisé Limo 	6 mm 1/4"		Opaco Matt	777971			
	9 mm 3/8"		Opaco Matt				777955
Pisé Mélange 	6 mm 1/4"		Opaco Matt	777972			
	9 mm 3/8"		Opaco Matt				777956
Pisé Ghiaia 	6 mm 1/4"		Opaco Matt	777973			
	9 mm 3/8"		Opaco Matt				777957

Manufacturer Details:
European Ceramics Approved
BPIR COMPLIANT

Importer Details:
European Ceramic Tiles Ltd
Address: 7A Cowley Place, Rosedale, AKL 0632
NZBN: 9429037294571
Website: euroceramics.co.nz

- Applicazione a parete
Wall application
- Applicazione a pavimento
Floor application

→ pag 134
Avvertenze
Warnings

	Spessore Thickness	Applicazione Application	Finitura Finish	120 x 280 cm 47 1/8" x 110 1/4"	30 x 30 cm 11 3/8" x 11 3/8"
Pisé Inserti A 	6 mm 1/4"	●	Opaco Matt	778012	
Pisé Inserti B 	6 mm 1/4"	●	Opaco Matt	778013	
Pisé Inserti C 	6 mm 1/4"	●	Opaco Matt	778014	
Inserti Mélange 	9 mm 3/8"	●	Opaco Matt		778015
Inserti Sabbia-Argilla 	9 mm 3/8"	●	Opaco Matt		778016
Inserti Limo-Ghiaia 	9 mm 3/8"	●	Opaco Matt		778017

Manufacturer Details:
European Ceramics Approved
BPIR COMPLIANT

Importer Details:
European Ceramic Tiles Ltd
Address: 7A Cowley Place, Rosedale, AKL 0632
NZBN: 9429037294571
Website: euroceramics.co.nz

COMPATTA / FLORIM

Fine porcelain stoneware
Rectified

9 mm 3/8" ↑

Technical features							
Dry-pressed ceramic tiles. Quality specifications, according to control tests of EN 14411-ISO 13006 Appendix G group B1a DGL			Standard requirements		Test results		Reference standard
			N ≥ 15 cm				
			(%)	(mm)	MATTE	GRIP	
	Length and width: deviation of the average size for each tile from the work size	Squadrato ISO 13006	± 0,3%	± 1 mm	± 0,15%		ISO 10545-2
	Thickness: deviation of the average thickness of each tile from the work size thickness	Squadrato ISO 13006	± 5%	± 0,5 mm	± 5%		
	Straightness: maximum deviation to the corresponding work sizes	Squadrato ISO 13006	± 0,3%	± 0,8 mm	± 0,10%		
	Orthogonality: permissible deviation in relation to the corresponding manufacturing dimensions	Squadrato ISO 13006	± 0,3%	± 1,5 mm	± 0,20%		
	Flatness: center curvature, edge curvature, and warpage in relation to the corresponding manufacturing dimensions	Squadrato ISO 13006	± 0,4%	± 1,8 mm	0,35%		
	Surface quality	A minimum of 95% of the tiles are to be free from visible defects			Compliant		
	Water absorption, percent mass fraction		≤ 0,5%	Average value 0,06%		ISO 10545-3	
	Breaking strength in N (thickness < 7,5 mm)		≥ 1300	Average value 2200 N		ISO 10545-4	
	Bending strength in N/mm²		≥ 35	Average value 50 N/mm²			
		Resistance to deep abrasion		≤ 175 mm³	Average value 140 mm³		ISO 10545-6
		Thermal shock resistance		Available testing method	Resistant		ISO 10545-9
		Resistance to staining		Available testing method	Class 4		ISO 10545-14
		Resistance to low concentrations of acids and alkali		See manufacturer's declaration	LA		ISO 10545-13
	Resistance to household chemicals and swimming pool salts		Minimum class B	A			
	Frost resistance		Required	Resistant		ISO 10545-12	
		Dynamic coefficient of friction		See manufacturer's declaration	≥ 0,42 wet		ANSI-A326.3
			See manufacturer's declaration	> 0,40		METODO BCRA	
	Shod ramp slipperiness		See manufacturer's declaration	R10 (10° < α ≤ 19°)	R11 (19° < α ≤ 27°)	DIN EN 16165 ANNEX B	
		Barefoot ramp slipperiness		See manufacturer's declaration	Class B (18° ≤ α < 24°)	Class C (α ≥ 24°)	DIN EN 16165 ANNEX A
		Pendulum test slipperiness		See manufacturer's declaration	PTV > 36 (slider 96)		BS EN 16165 ANNEX C

Manufacturer Details:
European Ceramics Approved
BPIR COMPLIANT

Importer Details:
European Ceramic Tiles Ltd
Address: 7A Cowley Place, Rosedale, AKL 0632
NZBN: 9429037294571
Website: euroceramics.co.nz

COMPATTA / FLORIMFine porcelain stoneware
Rectified

6 mm 2/8" ↑

Technical features						
Dry-pressed ceramic tiles. Quality specifications, according to control tests of EN 14411-ISO 13006 Appendix G group B1a DGL			Standard requirements		Test results	Reference standard
			N ≥ 15 cm			
			(%)	(mm)		
			MATTE			
	Length and width: deviation of the average size for each tile from the work size	Squadrate ISO 13006	± 0,3%	± 1 mm	± 0,15%	ISO 10545-2
	Thickness: deviation of the average thickness of each tile from the work size thickness	Squadrate ISO 13006	± 5%	± 0,5 mm	± 5%	
	Straightness: maximum deviation to the corresponding work sizes	Squadrate ISO 13006	± 0,3%	± 0,8 mm	± 0,10%	
	Orthogonality: permissible deviation in relation to the corresponding manufacturing dimensions	Squadrate ISO 13006	± 0,3%	± 1,5 mm	± 0,20%	
	Flatness: center curvature, edge curvature, and warpage in relation to the corresponding manufacturing dimensions	Squadrate ISO 13006	± 0,4%	± 1,8 mm	0,20%	
	Surface quality	A minimum of 95% of the tiles are to be free from visible defects.		Compliant		
	Water absorption, percent mass fraction		≤ 0,5%		Average value 0,08%	ISO 10545-3
	Breaking strength in N (thickness < 7,5 mm)		≥ 700		Average value 1350 N	ISO 10545-4
	Bending strength in N/mm ²		≥ 35		Average value 52 N/mm ²	
	Resistance to deep abrasion		≤ 175 mm ³		Average value 140 mm ³	ISO 10545-6
	Thermal shock resistance	Available testing method		Resistant		ISO 10545-9
	Resistance to staining	Available testing method		Class 4		ISO 10545-14
	Resistance to low concentrations of acids and alkali	See manufacturer's declaration		LA		ISO 10545-13
	Resistance to household chemicals and swimming pool salts	Minimum class B		A		
	Frost resistance	Required		Resistant		ISO 10545-12
	Release of hazardous substances	Declared value for GL surfaces intended for countertop applications		Compliant		DM 1-2-2007 Reg. CE 1935-2004
	Dynamic coefficient of friction	See manufacturer's declaration		≥ 0,42 wet		ANSI-A326.3
		See manufacturer's declaration		> 0,40		METODO BCRA
	Shod ramp slipperiness	See manufacturer's declaration		R10 (10° < α ≤ 19°)		DIN EN 16165 ANNEX B
	Barefoot ramp slipperiness	See manufacturer's declaration		Class B (18° ≤ α < 24°)		DIN EN 16165 ANNEX A
	Pendulum test slipperiness	See manufacturer's declaration		PTV > 36 (slider 96)		BS EN 16165 ANNEX C

Certificazioni | Certifications | Certifications | Prüfzeugnisse | Certificaciones | сертификации



放射性水平 A 类
Certification obligatoire pour l'exportation en Chine
Certification mandatory for export to China
Für den Export nach China obligatorische Zertifizierung
Certificazione obbligatoria per la esportazione a China
Обязательная сертификация для экспорта в Китай



FLORIM Ceramiche S.p.A.
via Cavallotti, 36 - 41042 Fiorano Modenese (MO) Italia



Manufacturer Details:
European Ceramics Approved
BPIR COMPLIANT

Importer Details:
European Ceramic Tiles Ltd
Address: 7A Cowley Place, Rosedale, AKL 0632
NZBN: 9429037294571
Website: euroceramics.co.nz

Fire Resistance

The building code relating to fire rating regulations and standards requires specifiers to provide documentation such as fire certificates for materials used in construction.

Ceramics are in itself a fire-resistant material, mostly being manufactured at over 1200 degrees Celsius. Testing and providing such certification are therefore not relevant to the Ceramics industry.

Ceramic and Porcelain tiles are an inert material, and therefore non-combustible. They do not release fumes or toxic gases in the event of a fire. Porcelain tiles contain no sealants, waxes or other chemicals that could release VOC's into the environment. Ceramics do not pose a risk of spreading or intensifying a fire therefore there is no testing required as they do not contribute to a fire.

EXTRAORDINARY EFFECTS DURING USE PHASE:

Fire: According to /EN 13501-1:2007+A1:2009/, ceramic tiles can be classified as A1 class of fire resistance rating, because they do not contribute to fire.

It has been demonstrated that the coating of the ceramic tiles, in case of fire, reduces heat on them and thus the risk of collapse.

Water: Ceramic tiles cannot react with water because they are an insoluble material.

For further information on the fire performance characteristics of ceramic/porcelain tiles or natural stone, please refer to the Technical Documents section on euroceramics.co.nz

Manufacturer Details:
European Ceramics Approved
BPIR COMPLIANT

Importer Details:
European Ceramic Tiles Ltd
Address: 7A Cowley Place, Rosedale, AKL 0632
NZBN: 9429037294571
Website: euroceramics.co.nz